

UP LIGHT


12V

MR16

35W

MODEL XU-3

Specification-grade landscape lighting, wet-location luminaire for uplighting or downlighting applications. For ground mounted, tree mounted or surface-mounted installations.



- Machined 6061-T6 copper-free aluminum.
- Five standard TGIC powder coat finishes available.
- Remote transformer required.
- Stainless steel hardware.
- 2' of 18/2 LV wire leads.
- 45° angled lens cap holds 3 lens accessories.
- Mount not included.
- Clear tempered borosilicate glass lens, glued in.
- High-temperature silicone O-ring seal used to seal the cap against the body.
- Molded silicone wire pass-thru attached to socket wire prevents wicking and water intrusion.
- ETL listed for wet location.
- Warranty: 10 Years.



Specifications

MODEL:	XU - 3	FINISHES:	BLK - Black	BZT - Bronze Texture
MATERIAL:	6061-T6 Aluminum		BZN - Bronze	BKBZ - Black Bronze
VOLTAGE:	12V		WHT - White	
WATTAGE:	35 Watt			
SOCKET:	GY 6.35 Bi-pin porcelain socket rated 600V, 250°C 18 ga, Teflon® coated leads.			

Ordering Logic:

MODEL	METAL	FINISH	
XU - 3	A - Aluminum	BLK - Black	BZT - Bronze Texture
		BZN - Bronze	BKBZ - Black Bronze
		WHT - White	

EXAMPLE: XU - 3 - A - BLK

PROJECT

TYPE

X-Light, Inc.